



# MULCHERS



AHM/240



ASM/200







**AMM/155**

## AMM

Pasture and crop residues are finely chopped and the swath evenly spread over the ground providing a mulch to improve soil moisture retention and seed germination.

### Features

- \* Clevis hitch cat 1 three point linkage
- \* Floating top link
- \* 4mm Body panel to withstand obstacle impact
- \* Blades pivoting on hardened bushes and grade 8 bolts
- \* Adjustable height skids
- \* Built-in mulching bar
- \* 6 series drive shaft with friction clutch



**AHM Sweet Potato Mulcher**

## SWEET POTATO SERIES

Additional features to the standard AMM and AHM mulchers

- \* Centrally mounted 3PL
- \* Park stands x 4 for storage
- \* Tine brackets on rear frame tube 850mm centres
- \* Tines laser cut out of bisalloy 400, 75x20mm section, 1500mm long with 10 adjusting holes
- \* Short Y blades over row

## AHM

### Typical applications:

Wheat, Maize, Sorghum, Rice and Cotton stubble.

Tobacco  
 Potato haulms  
 Pineapple tops  
 Pasture topping  
 Prunings ~ Macadamia and Grape  
 Banana plant prunings

### Features

- \* Double skin steel body panels to withstand obstacle impact
- \* Clevis hitch cat 1 and 2 three point linkage
- \* 4&6 x SPBX Section belt rotor drive on large diameter pulleys for optimum blade tip speed
- \* Series 8 drive shaft with friction clutch
- \* Floating top link

- \* 220mm (9") diameter rotor tube with 6 row blade configuration to reduce power requirements and even out belt loadings.
- \* Blades pivoting on hardened bushes and grade 8 bolts.
- \* 55mm diameter taper lock rotor support bearings.
- \* Fully adjustable rear flap to control swath spread.
- \* Adjustable height skids.



**AHM/240**



**AHM/285**



**ASM/200**

## ASM

Universal low clearance mulcher suitable for roadside grass maintenance, orchard and vineyard prunings

### Features

- \* Can be front or rear mounted on the tractor.
- \* Hydraulic side shift standard.
- \* Can be built LH or RH offset.
- \* 6 series drive shaft with friction clutch standard.
- \* Roller or castor wheels standard.
- \* 4 x SPBX section belt rotor drive on large dia pulleys for optimum blade tip speed.
- \* Hammers fitted standard, 'Y' flail option.
- \* 4mm thick plate monocoque body construction.
- \* Chain top link option.



# Mulcher Specifications

Model	Cutting Widths cm	Ins	Min Requirement kW	hp	No. Blades	Cutting Height cm	Weight kg	Transport Width	Options										
									Swath Deflectors	Friction Clutch	Rear Roller	Castor Wheels	Mulching Bar	1000 PTO Kit	Hammers	Flat Blade	Straight Blade	Y Blade	
ANM/155	155	61	23	30	32	2 - 10	490	177	O	S	O	O	S	N	N	O	O	S	
ANM/195	195	77	30	40	40	2 - 10	575	232	O	S	O	O	S	S	N	O	O	S	
AHM/160	160	63	37	50	36	2 - 10	710	187	O	S	O	O	O	O	N	O	O	O	S
AHM/195	195	77	44	60	48	2 - 10	815	222	O	S	O	O	O	O	N	O	O	O	S
AHM/240	240	94	51	70	60	2 - 10	925	267	O	S	O	O	O	O	N	O	O	O	S
AHM/285	285	112	60	85	72	2 - 10	1100	318	O	S	O	S	O	O	N	O	O	O	S
ASM/200*	200	79	37	50	18	2 - 10	760	232	N	S	S	O	SX2	O	O	S	N	N	O
ASM/265*	265	104	48	65	24	2 - 10	920	297	N	S	S	O	SX2	O	O	S	N	N	O
AOM/200	200	79	37	50	18	2 - 10	760	232	N	S	S	O	SX2	O	O	S	N	N	O
AOM/265	265	104	48	65	24	2 - 10	920	297	N	S	S	O	SX2	O	O	S	N	N	O
AHM/160F▲	160	63	51	70	18	2 - 10	980	187	N	S	S	O	N	S	S	S	N	N	O
AHM//195F▲	195	77	60	85	24	2 - 10	1100	222	N	S	S	O	N	S	S	S	N	N	O
AHM//240F▲	240	94	67	95	30	2 - 10	1250	272	N	S	S	O	N	S	S	S	N	N	O

\*ASM Models Fitted With Hydraulic Side Shift

▲Forestry Models Fitted With Heavy Duty Rotor & Additional Body Panels

**N = Not available**

**S = Standard**

**O = Option**

Manufactured by:

**AG - ENGINEERING PTY. LTD.**

ABN 15 168 153 419

Arkwright Crescent

Taree NSW 2430

TELEPHONE (02) 6552 6888 ~ FAX (02) 6551 0307

Email: [sales@agrifarm.com.au](mailto:sales@agrifarm.com.au)

Web site: [www.agrifarm.com.au](http://www.agrifarm.com.au)

Ag - Engineering's policy is to continually review machine designs to improve performance. We therefore reserve the right to vary the specifications to those shown on this brochure.

Your Dealer

