



®

BROADACRE MULCHERS



ACM/600



www.agrifarm.com.au

ACM

Typical Applications

Cotton Plants,
Cereal Crop Stubble
and Vegetable Remains.



ACM/600

Features

- * European gearbox C/W overrun clutch
- * 261 HP - ACM 400, 328 HP - ACM 600, 800 & 900
- * 2 x HD internal mulching bars
- * Cat '3' & Cat '4' Narrow Clevis hitch 3 PL
- * Sliding Top Hitch Point to follow undulations
- * 9 series European outer PTO shafts
- * 10 series European main PTO shaft
- * Y blades pivot on hardened steel bushes
- * 325 diameter rotor tube
- * Eight row blade configuration
- * High blade tip speed for optimum mulch
- * Opening rear shields
- * Height adjustable rear wheels -
2 x ACM/400 - 4 x ACM 600, 800 & 900
- * Automatic greasing system supplying
2 x rotor & 2 x jackshaft bearings -ACM/400
4 x rotor & 4 x jackshaft bearings -ACM/600, 800 & 900

SPECIFICATIONS

Model	Cutting Width		Min. Requirement		No. Blades	Cutting Height	Weight	Transport Width	Rear Wheels	Options
	cm	inch	kW	hp						
ACM/400	390	153	127	150	96	2-30	2730	420	2	○
ACM/600	608	232	149	185	144	2-30	4100	658	4	○
ACM/800	790	311	164	220	192	2-30	5466	840	4	○
ACM/900	890	350	179	240	216	2-30	6149	940	4	○

○ = Optional



ACM/600



Manufactured by:

AG - ENGINEERING PTY. LTD.

Arkwright Crescent Taree NSW 2430

Telephone 02 6552 6888

Fax 02 6551 0307

Email sales@agrifarm.com.au

Website www.agrifarm.com.au

ABN 15 168 153 419

Ag - Engineering's policy is to continually review machine designs to improve performance. We therefore reserve the right to vary the specifications to those shown on this brochure.

YOUR DEALER

